



SPECIFICATIONS
 Contact material: Brass
 Contact resistance: 30 milliohms max.
 Bushing material: Brass
 Housing material: Thermoplastic
 Insulation resistance: 100 megohms min.
 Withstanding: 500 VAC for 1 min.

Series	Style	Schematic	Bushing Plating	Terminal Plating	Housing/Insulator Color
CPRJ	P625	V	X	X	XX
RCA pin jack	Right angle PCB thru- hole mount	V=Mono with bypass switch	N=Nickel (std) G=Gold flash	T=Tin (std) S=Silver G=Gold flash	BK=Black GY=Gray RD=Red GR=Green WT=White OR=Orange YL=Yellow BN=Brown BL=Blue

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPRJ-P625-V-X-X-XX**

Description: RCA pin jack