


**SPECIFICATIONS**

Contact Resistance: 30mΩ max  
 Insulation Resistance: 100mΩ min at DC 500V  
 Withstanding: AC 500V for 1 min

Item	Name	Material
1	Earth Terminal	0.5T Brass
2	Terminal	0.5T Brass
3	Terminal	0.5T Brass
4	Base	ABS (WT is STD)
5	Cover	ABS (BK)
6	Washer	PBT
7	Washer	PBT

**Pin Hole Layout  
(Jack Bottom View)**



RoHS compliant

Series	Style-Ports	Schematic	Bushing Plating	Terminal Plating	Cover / Insulator Color
CPRJ	P621-X	A	X	X	XX/XX/XX
RCA pin jack	Right angle PCB thru-hole mount X=2,4,6	See Chart	N=Nickel (std) G=Gold flash	T=Tin (std) S=Silver G=Gold flash	BK=Black GY=Gray RD=Red Insulator Only: WT=White GR=Green YL=Yellow OR=Orange BL=Blue BN=Brown

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/10/05
				Checked	Lizzy	12/10/05
				Drawn	Tina	12/10/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPRJ-P681-2-A-X-X-XX/XX/XX**

Description: RCA pin jack