



SPECIFICATIONS
 Current / Voltage: 5A 125V
 Operation Limit Voltage: 200
 Withstanding: 1000 V
 Insulation Resistance: 1000 M Ω Min.
 Contact Resistance: 3 m Ω

| Item | Name | Material | Finish |
|------|------------|--------------|--------|
| 1 | B-355ZN | Zn Alloy | M-Ni |
| 2 | A-151BN-R | Copper Alloy | M-Ni |
| 3 | G-058BX-R | PA66+15%GF | Black |
| 4 | J-159BSA-R | Copper Alloy | M-Ag |
| 5 | C-112BN-R | Copper Alloy | M-Ni |
| 6 | B-352ZN | Zn Alloy | M-Ni |
| 7 | W-022FT-R | SPCC | M-Sn |
| 8 | M-083SN-R | Steel | M-Ni |
| 9 | H-131PX | PVC | Black |
| 10 | M-148FN-R | SPCC | M-Ni |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|----------------|-----------------|-----------------|
| | | | | Approved | Howard | 06/14/07 |
| | | | | Checked | Lizzy | 06/14/07 |
| | | | | Drawn | Tina | 06/14/07 |
| | | | | 0.0 \pm 0.35 | 0.00 \pm 0.20 | Angles \pm 3' |
| | | | | | | UNIT: mm |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPW-PLT187-PM-R**

Description: 7 Pin Connector Type PLT 187-PM-R