



- 1. Crimped ferrule: Hex crimp, size .128" (3.25mm)
- 2. Contact pin: Soldered

Item	Name	Material	Finish
1	Braid holder	Brass per QQ-B-626	Nickel plate 70μ" over copper strike
2	Insulator	Teflon, MIL-P-19468	White
3	Contact body	Beryllium copper per QQ-C-530	Gold flash over nickel plate 70μ" over copper strike
4	Spring	Beryllium copper per QQ-C-530	Nickel plate 70μ" over copper strike
5	Shell	Brass per QQ-B-626	Nickel plate 70μ" over copper strike
6	Contact pin	Brass per QQ-B-626	Gold flash over nickel plate 70μ" over copper strike
7	Ferrule	Brass, JIS H 3250, C 2700	Nickel plate 70μ" over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-1.0/2.3-R9901-BNTGG02**

Description: Crimp plug, 1.0/2.3, 75 ohms