



Item	Name	Material	Finish
1	Body	Brass	Nickel over copper
2	Hex body	Brass	Nickel over copper
3	Insulator	Teflon	White
4	Braid holder	Brass	Nickel over copper
5	Contact pin	Brass	Gold over nickel over copper
6	Spacer	Teflon	White
7	Spacer	Brass	Nickel over copper
8	Ferrule	Brass	Nickel over copper
9	Gasket	Rubber	Orange
10	Washer	SS41	Nickel over copper
11	Nut	Brass	Nickel over copper

RECOMMENDED
CABLE STRIPPING DIM'S

RECOMMENDED
MOUNTING HOLE

Hex crimp ferrule size 0.178"
Hex crimp contact size 0.068"
Panel thickness 3.5 mm max.

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/30/04
				Checked	Lizzy	04/30/04
				Drawn	Tina	04/30/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-7417-BNTGD18-WP**

Description: TNC bulkhead water proof crimp jack for RG-174/U, 188A/U and 316/U