


Item	Name	Material	Finish
1	Body	Brass Per QQ-B-626	Nickel PL 100 Min over Copper
2	Insulator	Teflon MIL-P-19468	White
3	Contact Pin	Beryllium Copper Per QQ-C-530	Gold PL 30 Min Over Nickel PL 70 Min Thick over Copper
4	Gasket	Silicone	Red
5	C Ring	SUS 304	Passivated
6	Shell	Brass Per QQ-B-626	Nickel PL 100 Min over Copper
7	Gasket	Silicone	Red
8	Washer	Brass Per QQ-B-613	Nickel PL 100 Min over Copper
9	Nut	Brass Per QQ-B-626	Nickel PL 100 Min over Copper

Max. Panel Thickness = 5.5mm

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/30/10
				Checked	Lizzy	12/30/10
				Drawn	Tina	12/30/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		



Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-7858CS-500BF00B**

Description: SMA Plug To Bulkhead Jack Adapter