


SPECIFICATIONS

- Interfaces per MIL-STD-348, Fig. 304-2
- Insulator Material: Teflon, ASTM-D-4894
- Gasket: Silicone Rubber, ZZ-R-765
- Lockwasher: Phosphor Bronze, !!-B-750
- Center Contact: Beryllium Copper, ASTM-B-196
- All Other Metal Parts: Brass, ASTM-B16
- Contact Finish: Gold Plating per MIL-G-45204
- All Other Finish: Silver Plating per QQ-S-365
- Impedance: 50 OHMS
- Operating Voltage: 1000 Volts RMS
- Frequency Range: DC to 11 GHz

.53 REF. ACROSS FLATS



RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/24/05
				Checked	Lizzy	01/24/05
				Drawn	Tina	01/24/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-A-301K**

Description: Adapter, F-F, Bulkhead, Angle, N