



SPECIFICATIONS

| | |
|----------------------------|--------------------------------|
| Impedance: | 50Ω |
| Interface Frequency Max.: | 6GHz |
| Insulation Resistance: | ≥5000MΩ |
| Outer Contact Resistance: | ≤2.5mΩ |
| Center Contact Resistance: | ≤5.0mΩ |
| Working Voltage: | 500V rms |
| Insertion Loss: | 0.15dB@DC-3GHz |
| VSWR: | ≤1.15@6GHz |
| Mating Numbers: | 500 |
| Weight: | 18.6g |
| Center Contact: | Beryllium Copper, Au Plating |
| Body: | Brass, Ni Plated |
| Shell: | Brass, Black Matte Powder Coat |
| Nut: | Brass, Black Matte Powder Coat |
| Insulator: | PTFE |
| Gasket: | Silicone Red |
| Operating Temp: | -50C to 155C |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 06/18/15 |
| | | | | Checked | Lizzy | 06/18/15 |
| | | | | Drawn | Tina | 06/18/15 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-ADT-40A500-BPCBG-A**

Description: N Male to MMCX Female Adapter