

SPECIFICATIONS

Temp.range: -65°C~+165°C
 Vibration: MIL-STD-202, Method 213
 Impedance: 50Ω
 Frequency Range: DC~3GHz
 Working Voltage: 335V max
 Withstand Voltage: 1000V rms
 Contact resistance
 Center Contact: ≤ 3 mΩ
 Outer Contact: ≤2 mΩ
 Insulation resistance: ≥ 5000 MΩ
 VSWR: Straight ≤ 1.2 (0~3GHz)
 Durability(mating): ≥500 (cycles)


MATERIAL & PLATING

Shell: brass black Chrome plated
 Inner conductor: Tin bronze gold plated
 insulators: PFTE
 o-ring: Silicone rubber

APPLICABLE STANDARD

MIL-C-39012;
 CECC 22110;
 IEC 60169-15..

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/07/14
				Checked	Lizzy	08/07/14
				Drawn	Tina	08/07/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-ADT-J3645-BBCTG-A**

Description: Adaptor TNC female to SMA female. Black Chrome Plating