



SPECIFICATIONS

Frequency Range: 0-1Ghz
 Normal Impedance: 75 OHMS
 Working Voltage: 500V Max.
 Proof Voltage: 1000V
 Temperature Range: -65°C~85°C
 Dielectric Material: PTFE (Teflon)
 Center Contact: Beryllium Copper
 Contact Finish: Gold Plating
 Gasket: Silicone Rubber
 All Other Parts: Brass
 All Other Finishes: Nickel Plated
 Operating Temp: -65°C ~ +85°C
 Thermal Shock: Per US Mil Std. 202.Method 107, Test B
 Salt Spray: Per US Mil Std. 202. Method 101, Test B
 Vibration: Per US Mil Srd. 202. Method 204, Test D

Item	Name	Material	Finish
1	Body	Zinc	Nickel
2	Insulator	PTFE	
3	Center Contact	Beryllium Copper	Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/31/08
				Checked	Lizzy	07/31/08
				Drawn	Tina	07/31/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-1998-BNTG-B**

Description: BNC Str. Jack PCB Mount