

RECOMMEND  
P.C.B LAYOUT

**SPECIFICATIONS**  
 Frequency Range: 0-1Ghz  
 Normal Impedance: 75 OHMS  
 Working Voltage: 500V Max.  
 Proof Voltage: 1000V  
 Temperature Range: -65°C~85°C  
 Dielectric Material: PTFE (Teflon)  
 Center Contact: Beryllium Copper  
 Contact Finish: Gold Plating  
 Gasket: Silicone Rubber  
 All Other Parts: Brass  
 All Other Finishes: Nickel Plated  
 Operating Temp: -65°C ~ +85°C  
 Thermal Shock: Per US Mil Std. 202.Method 107, Test B  
 Salt Spray: Per US Mil Std. 202. Method 101, Test B  
 Vibration: Per US Mil Srd. 202. Method 204, Test D

RoHS compliant


Item	Name	Material	Finish
1	Body	Zinc	Nickel
2	Insulator	PTFE	
3	Center Contact	Beryllium Copper	Gold

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/31/08
				Checked	Lizzy	07/31/08
				Drawn	Tina	07/31/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-19982**

Description: BNC Str. Jack PCB Mount



UNIT: mm