


**SPECIFICATIONS**

Vibration:	MIL-STD-202	VSWR Straight:	1.3 max.
Impedance:	50Ω	Durability:	500 cycles min.
Frequency Range:	DC~3GHz	Shell Material:	Brass, Nickel Plating
Working Voltage:	500V Max	Contact Pin:	Brass, Gold Plating
Withstanding Voltage:	1000V rms	Elastic Contact:	Tin Brass, Nickel Plated
Contact Resistance		Insulator:	PTFE or PE
Center Contact:	1.5mΩ max.	Crimp Ferrule:	Copper Alloy, Nickel Plating
Outer Contact:	1mΩ max.	O-Ring Sealing:	6146 Silastic
Insulation Resistance:	5000MΩ min.		

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/19/05
				Checked	Lizzy	12/19/05
				Drawn	Tina	12/19/05
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		



**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

**Part No.: CRF-BNC-7001-13BNDG001-R**

Description: BNC crimp plug, 75 ohm; for RG-179/U and RG-187A/U