



Recommended cable stripping dimensions

Name	Material	Finish
Body	Brass per QQ-B-626	Nickel plate 70 μ " over copper strike
Insulator	Delrin	White
Washer	SS41	Nickel plate 70 μ " over copper strike
Spring	SK5	Nickel plate 70 μ " over copper strike
C ring	SS41	Nickel plate 70 μ " over copper strike
Gasket	Rubber	Red
Shell	Brass per QQ-B-626	Nickel plate 70 μ " over copper strike
Contact pin	Brass per QQ-B-626	Gold plate 3 μ " over nickel plate 70 μ " over copper strike
Ferrule	Brass JIS H 3250, C 2700	Nickel plate 70 μ " over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 \pm 0.35	0.00 \pm 0.20	Angles \pm 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7001R-41BNDG-B**

Description: BNC crimp plug, 75 ohms