


RECOMMENDED
CABLE STRIPPING DIM'S

1. Crimped Ferrule:
Hex Crimp Size .213" (5.41mm)
2. Solder Contact Pin

Item	Name	Material	Finish	Item	Name	Material	Finish
1	Body	Brass	Nickel over Copper	6	Spring	SK5	Nickel over Copper
2	Insulator	Delrin	White	7	C Ring	SS41	Nickel over Copper
3	Contact Pin	Brass	Gold over Nickel over Copper	8	Gasket	Silicone	Red
4	Cube Body	SS41	Nickel over Copper	9	Shell	Brass	Nickel over Copper
5	Washer	SS41	Nickel over Copper	10	Nut	Brass	Nickel over Copper
				11	Ferrule	Brass	Nickel over Copper

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/12/09
				Checked	Lizzy	03/12/09
				Drawn	Tina	03/12/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		



Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NR-502CF00B**

Description: BNC Crimp Plug 75 ohms (for RG-55/U,142A/U,223/U,400/U)