



RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

CRIMPED FERRULE
Hex Crimp Size .178" (4.52mm)
CRIMPED CONTACT PIN
Hex Crimp Size .068" (1.72mm)

Item	Name	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	White
3	Washer	SS41	Nickel over Copper
4	Spring	SK5	Nickel over Copper
5	C Ring	SS41	Nickel over Copper
6	Gasket	Silicone	Red
7	Shell	Brass	Nickel over Copper
8	Contact Pin	Brass	Gold over Nickel over Copper
9	Spacer	Teflon	White
10	Spacer	Brass	Nickel over Copper
11	Ferrule	Brass	Nickel over Copper

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/15/11
				Checked	Lizzy	02/15/11
				Drawn	Tina	02/15/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NS-509BF000B**

Description: BNC Crimp Plug
(for RG-58C/U, 58/U)