



1. Crimped Ferrule:
Hex Crimp Size .429" (10.9mm)
2. Crimped Contact Pin
Hex Crimp Size .118" (3mm) or solder

RECOMMENDED
CABLE STRIPPING DIM'S

Item	Name	Material	Finish
1	Body	Brass	Nickel over Copper
2	Insulator	Teflon	White
3	Washer	SS41	Nickel over Copper
4	Washer	SK5	Nickel over Copper
5	C Ring	SS41	Nickel over Copper
6	Gasket	Silicone	Red
7	Shell	Brass	Nickel over Copper
8	Contact Pin	Brass	Gold over Nickel over Copper
9	Ferrule	Brass	Nickel over Copper

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/19/08
				Checked	Lizzy	03/19/08
				Drawn	Tina	03/19/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NS-516BF00B**

Description: BNC Crimp Plug 75 ohms (for B9913/LMR-400/B7810A/B8214)