



RECOMMENDED  
CABLE STRIPPING DIM'S

1. Crimped Ferrule:  
Hex Crimp Size .128" (3.25mm)

RoHS compliant

Item	Name	Material	Finish
1	Body	Brass	Nickel over Copper
2	Contact Pin	Phosphor Bronze	Gold over Nickel over Copper
3	Insulator	Delrin	White
4	Washer	SS41	Nickel over Copper
5	Spring	SK5	Nickel over Copper
6	C Ring	SS41	Nickel over Copper
7	Gasket	Silicone	Red
8	Shell	Zinc Diecast	Nickel over Copper
9	Contact Pin	Brass	Gold over Nickel over Copper
10	Ferrule	Brass	Nickel over Copper

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/12/09
				Checked	Lizzy	03/12/09
				Drawn	Tina	03/12/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NS-528ZF003B**

Description: BNC Crimp Plug 75 ohms (for RG-178B/U, 196A/U)