


RECOMMENDED  
CABLE STRIPPING DIM'S

1. Crimped Ferrule:  
Hex Crimp Size .324" (8.23mm)
2. Crimped Contact Pin:  
SQ Crimp Size .042" (1.07mm)

RoHS compliant

Item	Name	Material	Finish
1	Body	Brass	Nickel over Copper
2	Insulator	Teflon	White
3	Washer	SS41	Nickel over Copper
4	Spring	SK5	Nickel over Copper
5	C Ring	SS41	Nickel over Copper
6	Gasket	Silicone	Red
7	Shell	Brass	Nickel over Copper
8	Contact Pin	Brass	Gold over Nickel over Copper
9	Ferrule	Brass	Nickel over Copper

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/05/08
				Checked	Lizzy	12/05/08
				Drawn	Tina	12/05/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7011NS-729BF001B**  
 Description: BNC Crimp Plug 75 ohms