



- NOTES:
1. Crimped ferrule hex crimp size .178"
 2. Crimped contact pin hex crimp size .068"
 3. Max. panel thickness=3.5mm

Item	Name	Material	Finish
1	Hex body	Brass	Nickel pl 70µ" min thick over copper strike
2	Braid holder	Brass	Nickel pl 70µ" min thick over copper strike
3	Insulator	Teflon	White
4	Body	Brass	Nickel pl 70µ" min thick over copper strike
5	Contact pin	Brass	Gold pl 3µ" min over nickel pl 70µ" min thick over copper strike
6	Spacer	Teflon	White
7	Spacer	Brass	Nickel pl 70µ" min thick over copper strike
8	Ferrule	Brass	Nickel pl 70µ" min thick over copper strike
9	Gasket	Rubber	Red
10	Washer	SS41	Nickel pl 70µ" min thick over copper strike
11	Nut	Brass	Nickel pl 70µ" min thick over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/08/04
				Checked	Lizzy	10/08/04
				Drawn	Tina	10/08/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7023-11BNTG001**

Description: BNC bulkhead crimp jack