

RECOMMENDED
CABLE STRIPPING DIM'S


RECOMMENDED
MOUNTING HOLE

CRIMPED CONTACT PIN
HEX CRIMP SIZE .068" (1.72mm)

CRIMPED FERRULE
HEX CRIMP SIZE .178" (4.52mm)

Item	Name	Material	Finish
1	Nut	Brass	Nickel
2	Washer	SS41	Nickel
3	Gasket	Rubber	Orange
4	Ferrule	Brass	Nickel
5	Contact Pin	Brass	Gold
6	Braid Holder	Brass	Nickel
7	Insulator	Delrin	White
8	Hex Body	Brass	Nickel
9	Body	Brass	Nickel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/24/07
				Checked	Lizzy	10/24/07
				Drawn	Tina	10/24/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-7061DS-509CF006-B**

Description: BNC Bulkhead Crimp Jack (For RG-174/U, 188A/U, 316/U)