



SPECIFICATIONS

Voltage Rating:	500 V RMS
Contact Resistance:	3.0 Milliohms Max.
Insulation Resistance:	5000 Megohms Min
Withstanding:	1500 V RMS
Normal Impedance:	50 OHMS
Frequency Range:	0~1 GHz
Operating Temp:	-65°C to +165°C

Item	Name	Material
1	Conn. Body	Nickel Plating Over Zinc Alloy
2	Center Contact	Phosphor Bronze with Gold Plating at Contact Area, Tin Plating at Tail
3	Insulator	Polypropylene UL94HB
4	Grounding Terminal	Tin Plating Over Copper Wire
5	Mounting Hook	Tin Plating Over Brass

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/15/08
				Checked	Lizzy	07/15/08
				Drawn	Tina	07/15/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-BNC-DB950K-ZNPPBG-A**

Description: Dual Port BNC R/A PCB Mount Receptacle