



SPECIFICATIONS
 Current Rating: 15A AC/DC
 Voltage Rating: 600V AC/DC
 Temperature Range: -20C ~ +85C
 Contact Resistance: 10m ohm Max.
 Insulation Resistance: 1000M ohm Min.
 Withstanding: 500V AC/minute
 Protection Rating: IP68
 Housing Material: Plastic, UL94V-0, Black
 Contact Material: Copper Alloy
 Contact Plating: Gold over Nickel

Series	Type	Style	Pins	Plating
CRF	M12	AQ110K2	XX	GDXX
Connector	Type=M12	AQ1110K2	02,03,04	Gold Plating XX=Flash if blank 10, 60u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/11/12
				Checked	Lizzy	05/11/12
				Drawn	Tina	05/11/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-M12-AQ110K2-XX-XX**

Description: M12 Male 2~4P Snap in Waterproof Connector