



Assembly

SPECIFICATIONS

- Current Rating: 5.0A AC/DC
- Voltage Rating: 125V AC/DC
- Temperature Range: -40C ~ +85C
- Contact Resistance: 10m ohm Max.
- Insulation Resistance: 1000M ohm Min.
- Withstanding: 500V AC/minute
- Waterproof: IPX7
- Housing: PBT UL94V-0, Black
- Terminal: Brass
- O-Ring: EPDM, Black
- Nut: Brass

Series	Type	Style	Pins	Plating
CRF	M12	AQ120NA	XX	GDXX
Connector	Type=M12	AQ120NA	04,05	Gold Plating XX=Flash if blank 10, 60u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/30/11
				Checked	Lizzy	12/30/11
				Drawn	Tina	12/30/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-M12-AQ120NA-XX-GDXX**
 Description: M12 Cable Side Rec. Cross
 Type 4 Pos. Waterproof Connector