



MATED VIEW

SPECIFICATIONS

Impedance:	50Ω
Frequency Range:	0~3GHz
Working Voltage:	335V max
Withstanding Voltage:	1000V rms
Insertion Loss:	≤0.15 dB/6GHz
Center Contact Resistance:	≤3mΩ
Outer Contact Resistance:	≤2mΩ
Insulation Resistance:	≥5000MΩ
Durability:	>500
Temperature Range:	-40C ~ +85C

Name	Material	Finish
Body	Brass	Gold Plating
Center Conductor	Phosphor Bronze	Gold Plated
Gasket	Silicone Rubber	
Insulator	PTFE	

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/13/14
				Checked	Lizzy	10/13/14
				Drawn	Tina	10/13/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		



Central Components Manufacturing

440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MHF-20367-G-RL**

Description: MHFIII Plug Wire Mount Type (Height 1.6mm max) Gold Plating