



SPECIFICATIONS

- Impedance: 50Ω
- Frequency Range: DC ~ 6 GHz
- Working Voltage: 170V max
- Withstand Voltage: 500V rms
- Contact resistance
- Center Contact : ≤ 5 mΩ
- Outer Contact : ≤ 2.5 mΩ
- Insulation resistance: ≥ 1000 MΩ
- VSWR: ≤ 1.2 (0~4GHz)
- Durability(mating): ≥500 (cycles)
- Shell: brass, gold plated
- Elastic Contact: beryllium, gold plated
- Inner conductor: beryllium or tin brass, gold plated
- Insulator: PTFE
- Temperature range: -55°C ~ +155°C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/30/10
				Checked	Lizzy	08/30/10
				Drawn	Tina	08/30/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-26211A-BGTG-A**

Description: MMCX Crimp Jack RG174/U, 188A/U, 316/U