



Item	Name	Material	Finish
1	Center Contact	Brass	Gold
2	Insulator	Teflon	None
3	Link Lock	Brass	Gold
4	Body	Brass	Gold
5	Insulator	Teflon	None
6	Cover	Brass	Gold
7	Ferrule	Brass	Gold

SPECIFICATIONS
 Impedance: 50 Ohm
 Frequency Range: 0-6 GHz
 Withstanding: 500 VRMS Min.
 Durability: 500 Cycles Min.
 Temperature Range: -65C to +165C
 Crimp Ferrule
 Hex Crimp Size .128
 Solder Contact Pin

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/11/09
				Checked	Lizzy	12/11/09
				Drawn	Tina	12/11/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-9602-BGTG-A**

Description: MMCX Male Right Angle Crimp
 For RG-174/U,188A/U,316/U Cable