



CRIMPED FERRULE
Hex Crimp Size .128" (3.25mm)

SOLDER CONTACT PIN

Item	Name	Material	Finish
1	Body	Brass Per QQ-B-626	Gold PL 3 min over Nickel PL 70 min thick over Copper strike
2	Insulator	PTFE	White
3	Contact Pin	Brass Per QQ-B-626	Gold PL 30 min over Nickel PL 70 min thick over Copper Strike
4	C Ring	Beryllium Copper Per QQ-C-530	Gold PL 3 min over electroless nickel PL 120 min thick over Copper PL 60 min thick
5	Insulator	PTFE	White
6	Cover	Brass Per QQ-B-626	Gold PL 3 min over Nickel PL 70 min thick over Copper strike
7	Ferrule	Brass JIS H 3250, C 2700	Gold PL 3 min over Nickel PL 70 min thick over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	1/11/13
				Checked	Lizzy	1/11/13
				Drawn	Tina	1/11/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-9711NR-509BD000B**

Description: MMCX R/A Crimp Plug (for RG-174/U,188A/U,316/U)