



Crimped Ferrule  
Hex Crimp Size .128" (3.25mm)

Solder Contact Pin

RECOMMENDED  
CABLE STRIPPING DIM'S

| Item | Name        | Material         | Finish                       |
|------|-------------|------------------|------------------------------|
| 1    | Body        | Brass            | Gold over Nickel over Copper |
| 2    | Insulator   | Teflon           | White                        |
| 3    | Contact Pin | Brass            | Gold over Nickel over Copper |
| 4    | C Ring      | Beryllium Copper | Gold over Nickel over Copper |
| 5    | Ferrule     | Brass            | Gold over Nickel over Copper |
| 6    | Insulator   | Teflon           | White                        |
| 7    | Cover       | Brass            | Gold over Nickel over Copper |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing    | Name        | Date        |
|------|-------------|------|----------|------------|-------------|-------------|
|      |             |      |          | Approved   | Howard      | 11/21/07    |
|      |             |      |          | Checked    | Lizzy       | 11/21/07    |
|      |             |      |          | Drawn      | Tina        | 11/21/07    |
|      |             |      |          | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
|      |             |      |          |            |             | UNIT: mm    |

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-9711NR-528BD000B**

Description: MMXC R/A Crimp Plug (for RG-178B/U,196A/U)