



Crimped Ferrule
Hex Crimp Size .128" (3.25mm)
Solder Contact Pin

Item	Name	Material	Finish
1	Body	Brass	Gold PL 3 Over Nickel PL 70 min thick over copper strike
2	C Ring	Beryllium Copper	Gold PL 3 Over Nickel PL 70 min thick over copper strike
3	Insulator	Teflon	White
4	Braid Holder	Brass	Gold PL 3 Over Nickel PL 70 min thick over copper strike
5	Contact Pin	Brass	Gold PL 3 min over Nickel PL 70 min thick over copper strike
6	Ferrule	Brass	Gold PL 3 Over Nickel PL 70 min thick over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/02/06
				Checked	Lizzy	08/02/06
				Drawn	Tina	08/02/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-9711NS-509BP000B**

Description: MMCX Crimp Plug