



Crimped Ferrule:  
Hex Crimp Size .255"

Solder Contact Pin

RECOMMENDED  
CABLE STRIPPING DIM'S

| Item | Name         | Material | Finish                       |
|------|--------------|----------|------------------------------|
| 1    | Body         | Brass    | Nickel over Copper           |
| 2    | Braid Holder | Brass    | Nickel over Copper           |
| 3    | Insulator    | Teflon   | White                        |
| 4    | Contact Pin  | Brass    | Gold over Nickel over Copper |
| 5    | Gasket       | Silicone | Red                          |
| 6    | C Ring       | Brass    | Nickel over Copper           |
| 7    | Shell        | Brass    | Nickel over Copper           |
| 8    | Ferrule      | Brass    | Nickel over Copper           |
| 9    | Cover        | Brass    | Nickel over Copper           |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing    | Name        | Date        |
|------|-------------|------|----------|------------|-------------|-------------|
|      |             |      |          | Approved   | Howard      | 11/26/08    |
|      |             |      |          | Checked    | Lizzy       | 11/26/08    |
|      |             |      |          | Drawn      | Tina        | 11/26/08    |
|      |             |      |          | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
|      |             |      |          | UNIT: mm   |             |             |

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-N-7311NR-515BF002B**

Description: N R/A Crimp Plug (For 8X,LMR-240)