



5
RECOMMENDED
CABLE STRIPPING DIM'S

13.7
16.1
RECOMMENDED
MOUNTING HOLE

19 HEX
2.5
16.2
22

15.5
1.75

5/8-24UNEF-2A
13.4 A/F
22
28
3.65
22

1.1
18.3
3
ANNEALED AREA,
CRIMPING ACCEPTS

Item	Name	Material	Finish
1	Body	Brass	Nickel over Copper
2	Insulator	Teflon	White
3	Braid Holder	Brass	Gold over Nickel over Copper
4	Contact Pin	Phosphor Bronze	Gold over Nickel over Copper
5	Spacer	Teflon	White
6	Gasket	Rubber	Black
7	Washer	Brass	Nickel over Copper
8	Nut	Brass	Nickel over Copper

1.7
1.6
3

CRIMPED CONTACT PIN
Hex Crimp Size: .100" (2.54mm)
MAX PANEL THICKNESS: 6.5mm

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	5/31/10
				Checked	Lizzy	5/31/10
				Drawn	Tina	5/31/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-N-7362DS-524BF000B**

Description: N Bulkhead Direct Solder Jack