



Recommended Mounting Hole

Recommended Cable Stripping

**SPECIFICATIONS**

Operating Temp.: -65°C to +165°C  
 Vibration: MIL-STD-202, Method 213  
 Impedance: 50Ω  
 Working Voltage: 335 V max  
 Withstanding: 1000 V RMS  
 Contact Res. Center: 3 mΩ  
 Contact Res. Outer: 2 mΩ  
 Insulation Res.: 5000 M  
 VSWR: 1.15Ω  
 Durability: 500 cycles min.

Item	Name	Material	Finish
1	Body	Brass	Gold
2	Insulator	Teflon	
3	Nut	Brass	Gold
4	Washer	Phosphor Bronze	Gold
5	Gasket	Silicone	Orange
6	Center Pin	Beryllium Copper	Gold (3μ")

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/14/13
				Checked	Lizzy	08/14/13
				Drawn	Tina	08/14/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMA-727U-TBGG-002**

Description: SMA bulkhead jack for 0.085 RG405