



SPECIFICATIONS

Screws: M3 Steel Zinc Plated
 Contact: Phosphor Bronze
 Housing: PA66, UL94V-0
 Voltage Rating: 300V
 Current Rating: 15A
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding Voltage: AC1500V/1min
 Wire Range: 28-12AWG 2.5mm²
 Temp Range: -40C to +105C
 Max Soldering: +250C for 5 Sec
 Torque: 0.4Nm (3.6LB In)
 Strip Length: 7-8mm

Series	Type	Pitch	Positions	Color
CMTB	FE101F	XXX	XX	XX
Terminal blocks	Standard right angle plugable wire mount with mounting flange and screws	500=5.00mm 508=5.08mm 750=7.50mm 762=7.62mm	02-25	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FC100F-508-XX-GN**

Description: Standard right angle plug-able wire mount terminal block with mounting flange