


SPECIFICATIONS

Contact: Phosphor Bronze
 Screws: M2 Steel Zinc Plated
 Housing: PA66, UL94V-0
 Voltage Rating: 300V
 Current Rating: 8A
 Contact Resistance: 20mΩ
 Insulation Resistance: 5000MΩ/1000V
 Withstanding Voltage: AC1500V/1 Min
 Wire Range: 14-24 AWG 0.5-1.5mm²
 Temperature Range: -40C ~ +105C
 Max Soldering: +250C for 5 Sec
 Strut Length: 5-6mm

Series	Type	Pitch	Positions	Plating	Color
CMTB	FC420	XXX	XX	XX	XX
Terminal block	Pluggable R/A side screw	350=3.50mm 381=3.81mm 500=5.00mm 508=5.08mm (.200")	02-24	TN=Tin	GN=Green

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/02/04
				Checked	Lizzy	07/02/04
				Drawn	Tina	07/02/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-FC420-500-04-GN**

Description: Pluggable terminal block, right angle, side screw