



SPECIFICATIONS

Impedance: 50Ω
 Frequency Range: 0~12.4GHz
 Working Voltage: 1000V rms
 VSWR
 Straight: ≤1.1
 Right Angle: ≤1.2
 Contact Resistance
 Center Contact: ≤3mΩ
 Outer Contact: ≤2mΩ
 Insulation Resistance: ≤5000MΩ
 Body: Brass, Nickel Plating (Gold available)
 Center Conductor: Phosphor Bronze, Gold Plating
 O-Ring Seal: 6146 Silastic
 Insulator: PTFE
 Durability: >500
 Temperature Range: -55C ~ +155C
 Standards: MIL-C-39012/CECC22210/IEC 60169-16

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/12/15
				Checked	Lizzy	05/12/15
				Drawn	Tina	05/12/15
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: CRF-SMA-8655-BNTG-A

Description: SMA MALE EDGE MOUNT, TYPE 8655, FOR 0.062" THICK BOARD