



CRIMPED FERRULE
Hex Crimp Size .213" (5.41mm)

SOLDER CONTACT PIN

Max Panel Thickness: 3.2mm

RECOMMENDED
CABLE STRIPPING DIM'S

RECOMMENDED
MOUNTING HOLE

Item	Name	Material	Finish
1	Body	Brass Per QQ-B-626	Nickel PL 70 Min Thick Over Copper Strike
2	Insulator	Teflon MIL-P-19468	White
3	Contact Pin	Beryllium Copper Per QQ-C-530	Gold PL 30 Min Over Nickel PL 70 Min Thick Over Copper Strike
4	Ferrule	Brass JIS H 3250, C 2700	Nickel PL 70 Min Thick Over Copper Strike
5	Washer	SS41	Nickel PL 70 Min Thick Over Copper Strike
6	Nut	Brass Per QQ-B-626	Nickel PL 70 Min Thick Over Copper Strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	1/18/08
				Checked	Lizzy	1/18/08
				Drawn	Tina	1/18/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMA-97861BS-501BF-001B**

Description: SMA Bulkhead Crimp Jack (RG-58/U)