



SPECIFICATIONS

- Temp Range: -65C ~ +165C
- Vibration: MIL-STD-202, Method 213
- Impedance: 50Ω
- Frequency Range: DC~4GHz
- Working Voltage: 335V max
- Withstanding Voltage: 1000V rms
- Center Contact: ≤ 3mΩ
- Outer Contact: ≤ 2mΩ
- Insulation Resistance: ≤ 5000MΩ
- VSWR: ≤ 1.15 (0.8~2.5G)
- Durability: ≥ 500 Cycles
- Shell: Brass, Gold Plating
- Socket: Tin Brass, Gold Plating
- Elastic Contact: Tin Brass, Gold or Silver Plating
- Crimp Ferrule: Copper Alloy, Nickel or Gold Plating
- O-Ring Sealing: 6146 Silastic

APPLICABLE STANDARD

- MIL-C-39012
- CECC 22110
- IEC 60169-15

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/21/14
				Checked	Lizzy	10/21/14
				Drawn	Tina	10/21/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMA-CRY3300-BGTG-A**

Description: SMA Jack Type CRY3300, 50 Ohm