


SPECIFICATIONS

Interface: IEC61169-15
 Impedance: 50Ω
 Frequency Range: DC 6GHz
 Vswr: ≤1.2 (@3GHz)
 Withstanding: 750V AC
 Insulation Resistance: > 5000MΩ
 Conductor Resistance: < 2.0mΩ (outer)
 < 3.0mΩ (inner)
 Durability: 500 Cycles
 Operating Temp: -40C to +150C

Item	Name	Description
1	Body	Brass, Gold 3u" over Nickel 70u"
2	Insulator	PTFE
3	Insulator	PTFE
4	Inner Contact	Brass, Gold 3u" over Nickel 70u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/19/15
				Checked	Lizzy	03/19/15
				Drawn	Tina	03/19/15
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		



Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: CRF-SMA-RP-JWHD2900-BGTG-A

Description: RP-SMA Female (Male Pin) PCB Mount Right Angle Connector