



**SPECIFICATIONS**

- Temp.range: -55°C~+ 145°C
- Vibration: MIL-STD-202, Method 213
- Impedance: 50Ω
- Frequency Range: DC~3GHz
- Working Voltage: 335V max
- Withstand Voltage: 1000V rms
- Contact Resistance
- Center Contact: ≤ 3 mΩ
- Outer Contact: ≤2 mΩ
- Insulation resistance: ≥ 5000 MΩ
- VSWR: Right angle ≤ 1.20
- Durability(mating): ≥500 (cycles)

**MATERIAL & PLATING**

- Brass: Gold Plated
- Brass: Gold Plated

PTFE or PE  
 APPLICABLE STANDARD  
 MIL-C-39012;  
 CECC 22110;

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/15/10
				Checked	Lizzy	08/15/10
				Drawn	Tina	08/15/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMA-RP-KWE1065-BGTG-A**  
 Description: SMA Reverse Polarity Right Angle TYPE 1065 50 OHM