



SPECIFICATIONS

Impedance:	75 ohms
Frequency range:	0-4 GHz
Voltage rating:	250-335 volts
Withstanding:	750-1,000 VRMS for 1 min.
VSWR:	1.15-1.30 (18 dB to 23 dB)
Center contact resistance:	6 milliohms max.
Outer contact resistance:	2.5 milliohms max.
Insulator resistance:	1,000 megohms max.

Item	Description	Material	Finish
1	Body	Brass	Nickel
2	Body	Brass	Nickel
3	Body	Brass	Nickel
4	Pin	Beryllium copper	Gold 30μ"
5	Insulator	Teflon	White
6	C ring	Beryllium copper	
7	Ring	Brass	Nickel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMB-9101-B**

Description: SMB male crimp, 75 ohm, for RG174/U, RG188/U, RG316/U