



RECOMMENDED
CABLE STRIPPING DIM'S

CRIMPED FERRULE
Hex Crimp Size .128"
SOLDER CONTACT PIN

Item	Name	Material	Finish
1	Body	Brass Per QQ-B-626	Gold PL 3 Min over Nickel PL 70 Min Thick over Copper Strike
2	Insulator	Teflon MIL-P-19468	White
3	Contact Pin	Beryllium Copper per QQ-C-530	Gold PL 30 Min over Nickel PL 70 Min Thick over Copper Strike
4	Cube Body	Brass Per QQ-B-626	Gold PL 3 Min over Nickel PL 70 Min Thick over Copper Strike
5	C Ring	Beryllium Copper Per QQ-C-530	None
6	Shell	Brass Per QQ-B-626	Gold PL 3 Min over Nickel PL 70 Min Thick over Copper Strike
7	Ferrule	Copper JIS H 3300, C 1220	Gold PL 3 Min over Nickel PL 70 Min Thick over Copper Strike
8	Spacer	Teflon MIL-P-19468	White
9	Cover	Brass Per QQ-B-626	Gold PL 3 Min over Nickel PL 70 Min Thick over Copper Strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	02/10/10
				Checked	Lizzy	02/10/10
				Drawn	Tina	02/10/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMB-9111NR-711BD000B**

Description: SMB R/A Crimp Plug 75 Ohms (for RG-179/u,187A/U)