



1. Crimped ferrule hex crimp size .128" (3.25mm)
2. Contact pin to solder
3. Max. panel thickness 2.4mm

Item	Name	Material	Finish
1	Cube body	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper strike
2	Insulator	Teflon MIL-P-19468	White
3	Contact pin	Brass per QQ-B-626	Gold 30μ" over nickel 70μ" over copper strike
4	Body	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper strike
5	Washer	Brass per QQ-B-613	Gold 3μ" over nickel 70μ" over copper strike
6	Nut	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper strike
7	Ferrule	Brass JIS H 3250, C 2700	Gold 3μ" over nickel 70μ" over copper strike
8	Cover	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-SMC-9817-28BGTG001-R**

Description: SMC right angle bulkhead crimp jack