



Item	Name	Material	Finish
1	Main body	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper
2	Insulator	Teflon MIL-P-19468	White
3	Contact pin	Brass per QQ-B-626	Gold 30μ" over nickel 70μ" over copper
4	Gasket	Silicone	Black
5	Washer	Brass per QQ-B-613	Gold 3μ" over nickel 70μ" over copper
6	Nut	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper
7	Ferrule	Brass JIS H 3250, C 2700	Gold 3μ" over nickel 70μ" over copper
8	Cover	Brass per QQ-B-626	Gold 3μ" over nickel 70μ" over copper
9	Gasket	Silicone	Red

1. Crimped ferrule hex crimp size .128" (3.25mm)
2. Contact pin to solder
3. Max. panel thickness=2.4mm

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/20/06
				Checked	Lizzy	06/20/06
				Drawn	Tina	06/20/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm



Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: CRF-SMC-9817-28BGTG002-R

Description: SMC right angle bulkhead crimp jack, waterproof