



RECOMMENDED  
CABLE STRIPPING DIM'S

1. CRIMPED FERRULE  
HEX CRIMP SIZE .128" (3.25mm)
2. CRIMPED CONTACT PIN  
SQ. CRIMP SIZE .042" (1.06mm)

Name	Material	Finish
Body	SUS 316F	Passivated
Insulator	PTFE	White
Washer	SS41	Nickel PL 70 Min thick over Copper Strike
Washer	POM	Natural
C Ring	SS41	Nickel PL 70 Min Thick over Copper Strike
Gasket	Silicone	Red
Shell	SUS 316F	Passivated
Contact Pin	Brass Per QQ-B-626	Gold PL 10 Min over Nickel PL 70 Min Thick over Copper Strike
Ferrule	Brass JIS H 3250, C 2700	Nickel PL 70 Min Thick Over Copper Strike

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/11/13
				Checked	Lizzy	03/11/13
				Drawn	Tina	03/11/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-TNC-7411NS-711SS002B**

Description: TNC Crimp Plug (75 ohms) (for rg-179/U,187A/U)