



SPECIFICATIONS

Vibration: MIL-STD-202, Method 213
 Impedance: 50Ω
 Frequency Range: CD~3GHz
 Working Voltage: 500V max
 Withstanding Voltage: 1500V rms
 Contact Resistance
 center: ≤1.5mΩ
 outer: ≤1mΩ
 Insulation Resistance: ≥5000MΩ
 VSWR: ≤1.25
 Durability: ≥500 cycles
 Temperature Range: -65C ~ 165C

MATERIALS

Shell: Brass, Nickel Plating
 Socket: Tin Brass, Gold or Silver Plating
 Elastic Contact: Tin Brass, Gold or Silver Plating
 Insulator: PTFE or PE
 O-Ring: 6146 Silastic

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/13/06
				Checked	Lizzy	08/13/06
				Drawn	Tina	08/13/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-TNC-KWY1223-BGTG-A**

Description: TNC R/A Bulkhead Receptacle Jack