


Recommended P.C.Board Hole Layout



SPECIFICATIONS

- Current Rating: 1Amp
- Contact Material: Phosphor Bronze
- Contact Resistance: $20m\Omega$ Max
- Insulation Material: Polyester, UL94V-0
- Insulation Resistance: $1000M\Omega$ Min.
- Withstanding: 300V AC
- Operating Temp: $-40C$ to $+105C$

Series	Rows	Profile	Positions	Tail	Plating	Options
CRS	XX	LPA	XX	A	XX	XX
Receptacle Strip .05" x .05" (1.27mm x 1.27mm)	01=Single 02=Double	LPA=4.3mm Others available N=Narrow Body	Single row 2-40 Double row 4-100	A=Standard (2.3mm)	TN=Tin SGXX=Selective Gold GDXX=Gold XX=Flash if blank, 10,15,30u"	Blank=none SM=Surface mount PPL=Pick & Place TB=Tube TR=Tape & Reel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/29/05
				Checked	Lizzy	06/29/05
				Drawn	Tina	06/29/05
				0.0 ± 0.35	0.00 ± 0.20	Angles $\pm 3'$
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRS-01-LPA-N-XX-A-XX**

Description: 1.27 Pin Header Dual Rows Single Row DIP Type