



SPECIFICATIONS
 Current rating: 1 A
 Contact material: Phos. bronze
 Contact resistance: 20 milliohm max.
 Insulation material: Nylon 6T, UL 94V-0
 Insulation resistance: 1000 megohm min.
 Withstanding: 300 VAC
 Operating temp.: -40°C to +105°C

Series	Rows	Positions	Tail length	Plating	Options
CRS	XX	XX	X	XX	XX
0.5 X 0.5 receptacle strip	01=1 02=2	06-100	A=0.09" CS=Customer specified	TN=Tin SG=Selective gold GD=Gold	[Blank]=None P=Polarized CP=Centering pegs

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	8/10/99
				Checked	Lizzy	8/10/99
				Drawn	Tina	8/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				 UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRS-02-XX-A-XX-P-CP**

Description: .05" (1.27mm) receptacle strip, dual row with centering pegs, polarized