



**SPECIFICATIONS**

Contact material: Phosphor bronze  
 Contact plating: Gold flash over nickel  
 Insulator material: Nylon 6T, UL94V-0

Dimensions					
Pos.	A	B	Pos.	A	B
02	2.94	1.27	22	28.34	26.67
03	4.21	2.54	23	29.61	27.94
04	5.48	3.81	24	30.88	29.21
05	6.75	5.08	25	32.15	30.48
06	8.02	6.35	26	33.42	31.75
07	9.29	7.62	27	34.69	33.02
08	10.56	8.89	28	35.96	34.29
09	11.83	10.16	29	37.23	35.56
10	13.10	11.43	30	38.50	36.83
11	14.37	12.70	31	39.77	38.10
12	15.64	13.97	32	41.04	39.37
13	16.91	15.24	33	42.31	40.64
14	18.18	16.51	34	43.58	41.91
15	19.45	17.78	35	44.85	43.18
16	20.72	19.05	36	46.12	44.45
17	21.99	20.32	37	47.39	45.72
18	23.26	21.59	38	48.66	46.99
19	24.53	22.86	39	49.93	48.26
20	25.80	24.13	40	51.20	49.53
21	27.07	25.40			

Series	Rows	Contacts	Plating
CRS	02LDE	XX	XX
Receptacle strip, 1.27mm pitch	02LDE=Dual row, 2.1mm profile	2-40	GD=Gold TN=Tin SG=Selective gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRS-02LDE-XX-XX**

Description: Receptacle strip, 1.27mm pitch