



PCB LAYOUT / TOP VIEW

**SPECIFICATIONS**

Voltage Rating: 125V  
 Current Rating: 1.5A  
 Contact Resistance: 30 milliohms max.  
 Insulation Resistance: 500 megaohms min.  
 Withstanding: 1000V  
 Housing: PBT UL94V-0, Black  
 Conductor: 0.35mm Phos. Bronze  
 Plating: Gold Over Nickel In Contact  
 Tin Over Nickel in Solder Area  
 Temperature: -40C to +80C  
 Durability: 750 cycles min

**RoHS compliant**

Series	Positions	Contacts	Type	Color	Plating	Options
CTJ	X	XX	953	XX	PX	XX
Modular jack single position	4,6,8,10	02-10	Vertical Through Hole	BK=Black	P0=6u" P1=15u" P2=30u" P3=50u"	Blank=None WF=Without flange

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/07/09
				Checked	Lizzy	12/07/09
				Drawn	Tina	12/07/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-4-04-953-BK-P0**

Description: Modular Jack 953 4P4C Top Entry