

PCB LAYOUT / TOP VIEW

SPECIFICATIONS

Voltage Rating: 125V
 Current Rating: 1.5A
 Contact Resistance: 30 milliohms max.
 Insulation Resistance: 500 megaohms min.
 Withstanding: 1000V
 Housing: PBT UL94V-0, Black
 Conductor: 0.35mm Phos. Bronze
 Plating: Gold Over Nickel In Contact
 Tin Over Nickel in Solder Area
 Temperature: -40C to +80C
 Durability: 750 cycles min

RoHS compliant



Series	Positions	Contacts	Type	Color	Plating	Options
CTJ	X	XX	953	XX	PX	XX
Modular jack single position	4,6,8,10	02-10	Vertical Through Hole	BK=Black	P0=6u" P1=15u" P2=30u" P3=50u"	Blank=None WF=No Flange KY=Keyed

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/07/09
				Checked	Lizzy	12/07/09
				Drawn	Tina	12/07/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-4-04-953-BK-PX-XX**

Description: Modular Jack 953 4P4C Top Entry



Angles ± 3'

UNIT: mm